






Cat.no.:E-PS




Cat.no.:E-GGC




Cat.no.:E-CSS



Cat.no.:E-FSV




Cat.no.:TOBV



Cat.no.:E-CBV




Cat.no.:E-CV




Cat.no.:E-CBV




Cat.no.:E-FWBV



Cat.no.:E-FBV



Cat.no.:E-TMBV



Cat.no.:E-MSBV



NEWAY VALVE (SUZHOU) CO., LTD.

No.666 Taishan Road, Suzhou New District, P.R. China

Post Code: 215129


Tel: 86-512-666-15637

Fax: 86-512-666-18930-2102

E-mail: overseas.sales@neway.com.cn

<https://www.newayvalve.com>

Distributed by:



Cat.no.:E-MMBV-2025



Metal-Seated Ball Valves

Complete Solutions for Industrial Valves

NEWAY VALVE

Cat.no.:E-MMBV-2025

Table of Contents

Introduction

- 1 Quality Commitment
- 2~3 How To Order
- Metal-Seated Floating Ball Valve
 - 4 Design Feature
 - 5~6 Parts&Material
 - 7~10 Dimension&Weight
- Metal-Seated Trunnion Mounted Ball Valve
 - 11 Design Feature
 - 12~13 BSM Series Trunnion Mounted Ball Valve Parts & Material
 - 14~17 BSK Series Trunnion Mounted Ball Valve Parts & Material
 - 18~23 Dimension&Weight
- 24 Additional Feature Hardening Treatment FEA (finite element analysis)



Complete Solutions for Industrial Valves

As a global leader of valve manufacturing, Neway (SSE:603699) is dedicated to the production, research, and development of industrial valves. Neway is committed to providing complete valve solutions to all industries through advanced engineering and innovation.

Neway’s product line includes Ball, Butterfly, Gate, Globe, Check, Nuclear, Control, Subsea, Safety valves. Our high quality standards and innovative ability are recognized by many global end users and EPCs. Neway valves are utilized in a wide variety of industries and working conditions such as Refining, Chemical, Coal Chemical, Offshore(including subsea), Air Separation, LNG, Nuclear Power, Power Generation, and Pipeline Transmission applications.

Facilities & Service

Neway has developed a sophisticated multi-plant management system operating two valve assembly plants for GGC/ball/Butterfly/Nuclear valves, one API 6A valve plant, one safety valve plant, four casting & forging plants, and three R&D centers. Our largest assembly plant was expanded in 2013, and it covers 230,000 square meters.

Advanced software (ANSYS, FE-Safe, CF-Design, Siemens PLM and NX) is applied here at Neway for the Research & Development of products. We use SPA&MES to control the traceability and status of all products during the manufacturing process. In order to ensure the safety, reliability, and environmental compliance of our products, we use advanced testing equipments for fire safe, cryogenic, high pressure, and fugitive emission performance verification.

As part of Neway’s global strategy and to better serve our customers, we have established our overseas subsidiaries in the USA, the Netherlands, Italy, Singapore, Dubai, Nigeria, Vietnam, Malaysia, Qatar, and Saudi Arabia, along with over 80 agents and distributors worldwide.

Quality Assurance

Neway is dedicated to continuous improvement. We maintain a quality management system that encompasses our entire operation from order entry to final inspection. Through continuous efforts, Neway’s products have successfully obtained industry certifications, including ASME UV & NB, NBBI, KGS, CE, CCS, and BV approvals.

Quality Commitment

Neway recognizes the importance of valve quality for the safety and protection of personnel health and property. It is our quality commitment to focus our resources to provide our customers with first class products at a competitive price,that are designed, manufactured, inspected and tested in accordance with our customer’s specifications and that comply with all international standards.

With respect to the facts that the current industrial standards do not always take into consideration the likelihood and consequences of possible deterioration in service, related to specific service fluids or the external environment in which they operate. Our customers are requested to keep an open line of communication with our engineering department to identify and implement standards, that will provide valves with the possibility of deterioration in service, so as to ensure safety over the valves expected lifetime.



8

①

BSM

②

3

③

R

④

-

G

⑤

,

F316

⑥

/

45666

⑦

Neway part numbers are designed to cover essential features. When ordering, Please show the figure numbers and detailed description to avoid misunderstanding of your requirements.

Following descriptions provide a basic guideline in valve specification:

① Valve Size

Full bore

in	1/2	3/4	1	1-1/2	2	2-1/2	3	4	6	8	10	12
mm	15	20	25	40	50	65	80	100	150	200	250	300
in	14	16	18	20	24	26	28	30	32	34	36	40
mm	350	400	450	500	600	650	700	750	800	850	900	1000

Reduced bore

in	1/2x3/8	3/4x1/2	1x3/4	1-1/2x1	2x1-1/2	2-1/2x2	3x2	4x3	6x4	8x6	10x8	12x10
mm	15x10	20x15	25x20	40x25	50x40	65x50	80x50	100x80	150x100	200x150	250x200	300x250
in	14x12	16x14	18x16	20x18	24x20	26x24	28x24	30x24	32x30	34x30	36x30	40x36
mm	350x300	400x350	450x400	500x450	600x500	650x600	700x600	750x600	800x750	850x750	900x750	1000x900

② Valve type

Symbol	Valve type	Symbol	Valve type
BM	Side entry casting floating type metal seat	BSM	Side entry forging trunnion mounted type metal seat
BBM	Side entry casting floating type metal seat	BSK	Side entry forging trunnion mounted type(O-ring) metal seat

③ Class & Pressure

Code	Class	Pressure (Mpa)	Code	Class	Pressure (Mpa)
1	150	2	8	800	14
3	300	5	9	900	15
4	400	6.8	15	1500	25
6	600	10	25	2500	42

④ End Connection

Symbol	End	Symbol	End	Symbol	End
R	Raised face flanged end	B	Butt-weld end	N	Screwed end
J	RTJ flanged end	S	Socket weld end	SN	Socket weld/Screwed end

⑤ Operator

Symbol	Description	SSymbol	Description
	Lever	BS	Bare shaft
G	Gear operator	H	Hydraulic actuator
M	Electric actuator	L	Gas over oil actuator
P	Pneumatic actuator	D	Electric over oil actuator

⑥ Body Materials





Material	WCB	LCB	CF8	CF8M	CF3	CF3M	4A
Spec.No.	A216 Gr.WCB	A352 Gr.WCB	A351 Gr.CFB	A351 Gr.CF8M	A351 Gr.CF3	A351 Gr.CF3M	A890 Gr.4A

Material	A105N	LF2	F304	F316	F304L	F316L	F51
Spec.No.	A105N	A350 Gr.LF2	A182 Gr.F304	A182 Gr.F316	A182 Gr.F304L	A182 Gr.F316L	A182 Gr.F51


⑦ Trim Codes

Hard Face	Sealings	Stem	Ball	Seat
Material	Material	Material	Material	Material
Ball-WC Seat-TCC	O-Ring	17-4PH	F6a	F6a
Ball-NI60 Seat-NI55	Lip	F51	F304	F304
Ball-WC Seat-NI55	Graphite	F53	A105N/ENP	A105N/ENP
Ball -Cr3C2-NiCr		Inconel 718	17-4PH	17-4PH
Seat -Cr3C2-NiCr		Monel k500	AISI 4140/ENP	AISI 4140/ENP
Ball-TCC Seat-NI60			F316	F316
			F304L	F304L
			F316L	F316L
			LF2/ENP	LF2/ENP
			F51	F51


Note: Materials are according to customer requirements for reference.



ITEM	PART	CRABON STEEL	STAINLESS STEEL
P01	BODY	ASTMA105N	ASTMA182 F316
P02	BODY CAP	ASTMA105N	ASTMA182 F316
P03	STEM	ASTMA705 630	ASTMA182 F51
P05	GLAND FLANGE	ASTMA216 WCB	ASTMA351 CF8M
P06	GLAND	ASTMA276 316/316L	ASTMA276 316/316L
PO7	STUD	ASTMA193 B7M	ASTMA193 B8M CI2
P07a	STUD	ASTMA193 B7M	ASTMA193 B8M CI2
P08	NUT	ASTMA194 2HM	ASTMA194 8M
P08a	NUT	ASTMA1942HM	ASTMA194 8M
C01	BALL	ASTMA182 F316/F316L+WC	ASTMA182 F316/F316L+WC
C02	SEAT	ASTMA182 F316/F316L+WC	ASTMA182 F316/F316L+WC
S01	GASKET	316L+GRAPHITE	316L+GRAPHITE
S04	PACKING	GRAPHITE	GRAPHITE
S04b	SEAT PACKING	GRAPHITE	GRAPHITE
W02	SPRING	ASTM B637 UNS NO7750	ASTM B637 UNS NO7750
W49	SEAT RETAINER RING	ASTMA182 F316/F316L	ASTMA182 F316/F316L
W26a	THRUST WASHER	ASTMA240316/316L+NITRIDING	ASTMA240 316/316L+NITRIDING
N05	GEAR BOX	DUCTILE IRON	DUCTILE IRON
N09	BOLT	ISO 8988	ISO 3506 A2-70
N09a	BOLT	ISO 898 8.8	ISO 3506 A2-70
N35	YOKE	ASTMA572 Gr50	ASTMA572 Gr50



- 1 Top flange design as per ISO 5211, optional actuators of gearbox, electric actuator and pneumatic actuator are available.
- 2 Hard faced ball and the seat to satisfy the requirement of high hardness, high temperature resistance, wear resistance.
- 3 With the help of the pre-loaded spring, the seat is able to maintain seal even in low operating pressure.
- 4 Several designs of the seat to choose from, among which the dust proof seat design is available.



Class 150 Full bore (Floating)


Size		D		L				H		W		V		Weight	
				RF		BW									
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg
1/2	15	0.51	13	4.25	108	5.49	139.5	2.23	56.6			5.51	140	4.41	2
3/4	20	0.75	19	4.61	117	6.00	152.5	2.32	59			5.51	140	6.61	3
1	25	0.98	25	5.00	127	6.50	165	3.29	83.5			8.46	215	8.82	4
1-1/2	40	1.50	38	6.50	165	7.52	191	4.63	117.5			10.43	265	17.64	8
2	50	2.01	51	7.01	178	8.50	216	5.15	130.8			16.93	430	22.05	10
3	80	2.99	76	7.99	203	11.14	283	6.90	175.3			41.73	1060	35.27	16
4	100	4.02	102	9.02	229	12.01	305	7.65	194.3			41.73	1060	88.18	40

Class 150 Reduced bore (Floating)

Size		D		d		L				H		W		V		Weight	
						RF		BW									
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg
1/2*3/8	15*10	0.51	13	0.28	7	4.25	108	5.49	139.5	1.93	49			5.51	140	3.31	1.5
3/4*1/2	20*15	0.75	19	0.51	13	4.61	117	6.00	152.5	2.23	56.6			5.51	140	4.41	2
1*3/4	25*20	0.98	25	0.75	19	5.00	127	6.50	165	2.32	59			5.51	140	6.61	3
1-1/2*1	40*25	1.50	38	0.98	25	6.50	165	7.52	191	3.29	83.5			8.46	215	15.43	7
2*1-1/2	50*40	2.01	51	1.50	38	7.01	178	8.50	216	4.63	117.5			10.43	265	17.64	8
3*2	80*50	2.99	76	2.01	51	7.99	203	11.14	283	5.15	130.8			10.43	265	30.86	14
4*3	100*80	4.02	102	2.99	76	9.02	229	12.01	305	6.90	175.3			16.93	430	79.37	36

Class 300 Full bore (Floating)

Size		D		L				H		W		V		Weight	
				RF		BW									
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg
1/2	15	0.51	13	5.51	140	5.51	140	2.23	56.6			5.51	140	6.61	3
3/4	20	0.75	19	5.98	152	5.98	152	2.32	59			5.51	140	8.82	4
1	25	0.98	25	6.50	165	6.50	165	3.29	83.5			8.46	215	13.23	6
1-1/2	40	1.50	38	7.52	191	7.52	191	4.63	117.5			10.43	265	24.25	11
2	50	2.01	51	8.50	216	8.50	216	5.15	130.8			16.93	430	33.07	15
3	80	2.99	76	11.14	283	11.14	283	6.90	175.3			41.73	1060	103.62	47
4	100	4.02	102	12.01	305	12.01	305	10.04	255	11.81	300			149.91	68



Class 300 Reduced bore (Floating)


Size		D		d		L				H		W		V		Weight	
						RF		BW									
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg
1/2*3/8	15*10	0.51	13	0.28	7	5.51	140	5.51	140	2.14	54.3			5.51	140	4.41	2
3/4*1/2	20*15	0.75	19	0.51	13	5.98	152	5.98	152	2.23	56.6			5.51	140	6.61	3
1*3/4	25*20	0.98	25	0.75	19	6.50	165	6.50	165	2.32	59			5.51	140	8.82	4
1-1/2*1	40*25	1.50	38	0.98	25	7.52	191	7.52	191	3.29	83.5			8.46	215	19.84	9
2*1-1/2	50*40	2.01	51	1.50	38	8.50	216	8.50	216	4.63	117.5			10.43	265	28.66	13
3*2	80*50	2.99	76	2.01	51	11.14	283	11.14	283	5.15	130.8			16.93	430	99.21	45
4*3	100*80	4.02	102	2.99	76	12.01	305	12.01	305	6.90	175.3			41.73	1060	143.30	65

Class 400 Full bore (Floating)

Size		D		L						H		W		V		Weight	
				RF		BW		RTJ									
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg
1/2	15	0.51	13	6.50	165	6.50	165	6.46	164	3.86	98			5.91	150	8.82	4
3/4	20	0.75	19	7.52	191	7.52	191	7.52	191	4.53	115			7.09	180	13.23	6
1	25	0.98	25	8.50	216	8.50	216	8.50	216	4.74	120.5			10.43	265	24.25	11
1-1/2	40	1.50	38	9.49	241	9.49	241	9.49	241	6.26	159			11.81	300	55.11	25
2	50	2.01	51	11.50	292	11.50	292	11.61	295	11.34	288	11.81	300			110.23	50
3	80	2.99	76	14.02	356	14.02	356	14.13	359	11.89	302	15.75	400			121.25	55
4	100	4.02	102	15.98	406	15.98	406	16.14	410	12.60	320	23.62	600			414.46	188

Class 400 Reduced bore (Floating)

Size		D		d		L						H		W		V		Weight	
						RF		BW		RTJ									
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg
1/2*3/8	15*10	0.51	13	0.28	7	6.50	165	6.50	165	6.46	164	3.19	81			5.91	150	6.61	3
3/4*1/2	20*15	0.75	19	0.51	13	7.52	191	7.52	191	7.52	191	3.86	98			5.91	150	11.02	5
1*3/4	25*20	0.98	25	0.75	19	8.50	216	8.50	216	8.50	216	4.53	115			7.09	180	19.84	9
1-1/2*1	40*25	1.50	38	0.98	25	9.49	241	9.49	241	9.49	241	4.74	120.5			10.43	265	48.50	22
2*1-1/2	50*40	2.01	51	1.50	38	11.50	292	11.50	292	11.61	295	6.26	159			11.81	300	55.11	25
3*2	80*50	2.99	76	2.01	51	14.02	356	14.02	356	14.13	359	11.34	288	11.81	300			112.43	51
4*3	100*80	4.02	102	2.99	76	15.98	406	15.98	406	16.14	410	11.89	302	15.75	400			399.03	181



Class 600 Full bore (Floating)

Size		D		L						H		W		V		Weight	
				RF		BW		RTJ									
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg
1/2	15	0.51	13	6.50	165	6.50	165	6.46	164	3.86	98			5.91	150	8.82	4
3/4	20	0.75	19	7.52	191	7.52	191	7.52	191	4.53	115			7.09	180	13.23	6
1	25	0.98	25	8.50	216	8.50	216	8.50	216	4.74	120.5			10.43	265	24.25	11
1-1/2	40	1.50	38	9.49	241	9.49	241	9.49	241	6.26	159			11.81	300	55.11	25
2	50	2.01	51	11.50	292	11.50	292	11.61	295	11.34	288	11.81	300			110.23	50
3	80	2.99	76	14.02	356	14.02	356	14.13	359	11.89	302	15.75	400			121.25	55
4	100	4.02	102	17.01	432	17.01	432	17.13	435	12.60	320	23.62	600			414.46	188

Class 600 Reduced bore (Floating)


Size		D		d		L						H		W		V		Weight	
						RF		BW		RTJ									
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg
1/2*3/8	15*10	0.51	13	0.28	7	6.50	165	6.50	165	6.46	164	3.23	82			5.91	150	6.61	3
3/4*1/2	20*15	0.75	19	0.51	13	7.52	191	7.52	191	7.52	191	3.86	98			5.91	150	11.02	5
1*3/4	25*20	0.98	25	0.75	19	8.50	216	8.50	216	8.50	216	4.53	115			7.09	180	19.84	9
1-1/2*1	40*25	1.50	38	0.98	25	9.49	241	5.55	241	9.49	241	4.74	120.5			10.43	265	48.50	22
2*1-1/2	50*40	2.01	51	1.50	38	11.50	292	7.56	292	11.50	292	6.26	159			11.81	300	55.11	25
3*2	80*50	2.99	76	2.01	51	14.02	356	14.02	356	14.13	359	11.34	288	11.81	300			112.43	51
4*3	100*80	4.02	102	2.99	76	17.01	432	17.01	432	17.13	435	11.89	302	15.75	400			399.03	181

Class 900 Full bore (Floating)

Size		D		L						H		W		V		Weight	
				RF		BW		RTJ									
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg
1/2	15	0.51	13	8.50	216	8.50	216	8.50	216	4.41	112			7.09	180	22.05	10
3/4	20	0.75	19	9.02	229	9.02	229	9.02	229	4.75	120.5			10.43	265	28.66	13
1	25	0.98	25	10.00	254	10.00	254	10.00	254	6.24	158.5			11.81	300	33.07	15
1-1/2	40	1.50	38	12.01	305	12.01	305	12.01	305	7.48	190			15.75	400	105.82	48
2	50	2.01	51	14.49	368	14.49	368	14.61	371	11.42	290	15.75	400			158.73	72

Class 900 Reduced bore (Floating)

Size		D		d		L						H		W		V		Weight	
						RF		BW		RTJ									
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg
1/2*3/8	15*10	0.51	13	0.28	7	8.50	216	8.50	216	8.50	216	4.17	106			6.50	165	17.64	8
3/4*1/2	20*15	0.75	19	0.51	13	9.02	229	9.02	229	9.02	229	4.41	112			7.09	180	19.84	9
1*3/4	25*20	0.98	25	0.75	19	10.00	254	10.00	254	10.00	254	4.74	120.5			10.43	265	26.46	12
1-1/2*1	40*25	1.50	38	0.98	25	12.01	305	12.01	305	12.01	305	6.24	158.5			11.81	300	30.86	14
2*1-1/2	50*40	2.01	51	1.50	38	14.49	368	14.49	368	14.61	371	7.49	190			15.75	400	99.21	45



Class 1500 Full bore (Floating)

Size		D		L						H		W		V		Weight	
				RF		BW		RTJ									
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg
1/2	15	0.51	13	8.50	216	8.50	216	8.50	216	4.41	112			7.09	180	22.05	10
3/4	20	0.75	19	9.02	229	9.02	229	9.02	229	4.25	120.5			10.43	265	28.66	13
1	25	0.98	25	10.00	254	10.00	254	10.00	254	6.24	158.5			11.81	300	33.07	15
1-1/2	40	1.50	38	12.01	305	12.01	305	12.01	305	7.49	190			15.75	400	105.82	48
2	50	2.01	51	14.49	368	14.49	368	14.61	371	11.42	290	15.75	400			158.73	72

Class 1500 Reduced bore (Floating)


Size		D		d		L						H		W		V		Weight	
						RF		BW		RTJ									
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg
1/2*3/8	15*10	0.51	13	0.28	7	8.50	216	8.50	216	8.50	216	4.17	106			6.50	165	17.64	8
3/4*1/2	20*15	0.75	19	0.51	13	9.02	229	9.02	229	9.02	229	4.41	112			7.09	180	19.84	9
1*3/4	25*20	0.98	25	0.75	19	10.00	254	10.00	254	10.00	254	4.74	120.5			10.43	265	26.46	12
1-1/2*1	40*25	1.50	38	0.98	25	12.01	305	12.01	305	12.01	305	6.24	158.5			11.81	300	30.86	14
2*1-1/2	50*40	2.01	51	1.50	38	14.49	368	14.49	368	14.61	371	7.48	190			15.75	400	99.21	45

Class 2500 Full bore (Floating)


Size		D		L						H		W		V		Weight	
				RF		BW		RTJ									
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg
1/2	15	0.51	13	10.39	264	10.39	264	10.39	264	4.53	115			7.09	180	26.46	12
3/4	20	0.75	19	10.75	273	10.75	273	10.75	273	4.65	118			10.43	265	35.27	16
1	25	0.98	25	12.13	308	12.13	308	12.13	308	6.97	177			11.81	300	41.89	19
1-1/2	40	1.50	38	14.49	368	14.49	368	14.49	368	8.03	204			15.75	400	108.02	49
2	50	1.65	42	17.76	451	17.76	451	17.87	454	11.73	298	15.75	400			169.75	77

Class 2500 Reduced bore (Floating)

Size		D		d		L						H		W		V		Weight	
						RF		BW		RTJ									
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg
1/2*3/8	15*10	0.51	13	0.28	7	10.39	264	10.39	264	10.39	264	3.70	94			6.30	160	19.84	9
3/4*1/2	20*15	0.75	19	0.51	13	10.75	273	10.75	273	10.75	273	4.53	115			7.09	180	26.46	12
1*3/4	25*20	0.98	25	0.75	19	12.13	308	12.13	308	12.13	308	4.65	118			10.43	265	34.17	15.5
1-1/2*1	40*25	1.50	38	0.98	25	14.49	368	14.49	368	14.49	368	6.97	177			11.81	300	92.59	42
2*1-1/2	50*40	1.65	42	1.50	38	17.76	451	17.76	451	17.87	454	8.03	204			15.75	400	152.12	69



- 1 Top flange design as per ISO 5211, optional actuators of gearbox, electric actuator and pneumatic actuator are available.
- 2 Low emission graphite packing design.
- 3 Hard faced ball and the seat to satisfy the requirement of high hardness, high temperature resistance, wear resistance.
- 4 With the help of the pre-loaded spring, the seat is able to maintain seal even in low operating pressure.
- 5 Several designs of the seat to choose from, among which the dust proof seat design is available.




ITEM	PART	CRABON STEEL	STAINLESS STEEL
P01	BODY	ASTMA105N	ASTM A182 F316
P02	BODY CAP	ASTMA105N	ASTM A182 F316
P03	STEM	ASTMA705630	ASTM A182 F51
P04	TRUNNION	ASTM A705 630	ASTM A182 F51
P05	GLAND FLANGE	ASTMA216 WCB	ASTMA351 CF8M
P06	GLAND	ASTMA276316/316L	ASTMA276316/316L
P07	STUD	ASTMA193 B7M	ASTM A193 B8M CI2
P07a	STUD	ASTM A193 B7M	ASTM A193 B8M CI2
P07c	STUD	ASTM A193 B7M	ASTM A193 BSM CI2
P08	NUT	ASTM A194 2HM	ASTM A194 8M
P08a	NUT	ASTM A194 2HM	ASTM A194 8M
P08c	NUT	ASTM A194 2HM	ASTM A194 8M
P10b	SCREW	ASTM A193 B7M	ASTM A193 B8M CI2
P15	DRAIN PLUG	ASTMA182 F316/F316L	ASTMA182 F316/F316L
P19	COVER	ASTM A105N	ASTMA182 F316/F316L
P21	COVER FLANGE	ASTM A105N	ASTMA182 F316/F316L
C01	BALL	ASTM A182 F316/F316L+WC	ASTM A182 F316/F316L+WC
C02	SEAT	ASTM A182 F316/F316L+WC	ASTM A182 F316/F316L+WC
S01	GASKET	316L+GRAPHITE	316L+GRAPHITE
S01c	GASKET	316L+GRAPHITE	316L+GRAPHITE
S01d	GASKET	316L+GRAPHITE	316L+GRAPHITE
S01k	GASKET	316L+GRAPHITE	316L+GRAPHITE
S04	PACKING	GRAPHITE	GRAPHITE
S04b	SEAT PACKING	GRAPHITE	GRAPHITE
S09	FIRE SAFE GRAPHITE	GRAPHITE	GRAPHITE
W01	SPRING	ASTM B637 UNS NO7750	ASTM B637 UNS NO7750
W49	SEAT RETAINER RING	ASTMA182 F316/F316L	ASTMA182 F316/F316L
W26a	THRUST WASHER	ASTM A240 316/316L+NITRIDING	ASTM A240 316/316L+NITRIDING
N05	GEAR BOX	DUCTILE IRON	DUCTILE IRON
N07d	STUD	ISO8988.8	ISO 3506 A2-70
N08d	NUT	ISO 8988	ISO 3506 A2-70
N10c	BOLT	ISO 898 8.8	ISO 3506 A2-70
N30	BEARING	ASTM A240 316/316L+NITRIDING	ASTM A240 316/316L+NITRIDING
N30b	BEARING	ASTM A240 316/316L+NITRIDING	ASTM A240 316/316L+NITRIDING
N35	YOKE	ASTMA572 Gr50	ASTMA572 Gr50
N93	LIFTING LUG	ASTMA572 Gr50	ASTMA572 Gr50
N92	SUPPORT LEG	ASTMA572 Gr50	ASTMA572 Gr50
N109	CAGE	ASTMA705 630	ASTM A182 F51

BSK Series Trunnion Mounted Ball Valve

O Ring Stem Seal

Parts & Material



Parts & Material

BSK Series Trunnion Mounted Ball Valve


O Ring Stem Seal

ITEM	PART	CRABON STEEL	STAINLESS STEEL
P01	BODY	ASTM A105N	ASTM A182 F316
P02	BODY CAP	ASTM A105N	ASTM A182 F316
P03	STEM	ASTMA705 630	ASTMA182 F51
P07	STUD	ASTMA193 B7M	ASTMA193 B8MCI2
P08	NUT	ASTMA194 2HM	ASTM A194 8M
P10b	SCREW	ASTM A193 B7M	ASTM A193 B8M CI2
P10c	SCREW	ASTM A193 B7M	ASTM A193 B8M CI2
P14	STEM INJECTION	ASTM A182 F316/F316L	ASTMA182 F316/F316L
P14a	SEAT INJECTION	ASTM A182 F316/F316L	ASTMA182F316/F316L
P15	DRAIN PLUG	ASTM A182 F316/F316L	ASTMA182 F316/F316L
P16	CHECK VALVE	ASTM A182 F316/F316L	ASTM A182 F316/F316L
P18	VENT VALVE	ASTM A182 F316/F316L	ASTMA182F316/F316L
P19	COVER	ASTM A105N	ASTMA182F316/F316L
C01	BALL	ASTM A182 F316/F316L+WC	ASTM A182 F316/F316L+WC
C02	SEAT	ASTMA182 F316/F316L+WC	ASTM A182 F316/F316L+WC
S01	GASKET	316L+GRAPHITE	316L+GRAPHITE
S01a	GASKET	316L+GRAPHITE	316L+GRAPHITE
S01c	GASKET	316L+GRAPHITE	316L+GRAPHITE
S02	O RING	FKM	FKM
S02a	O RING	FKM	FKM
S02c	O RING	FKM	FKM
S02e	O RING	FKM	FKM
S02g	O RING	FKM	FKM
S02h	O RING	FKM	FKM
S04	PACKING	GRAPHITE	GRAPHITE
W01	SPRING	ASTM B637 UNS NO7750	ASTM B637 UNS NO7750
W03	ANTI-STATIC PLUNGER	ASTM A276316	ASTM A276316
W04	ANTI-STATIC BALL	ASTM A276 316	ASTM A276 316
W05	ANTI-STATIC SPRING	ATSM A313 316	ATSM A313 316
W26a	THRUST WASHER	RPTFE	RPTFE
W53	SEAT FOLLOWER	ASTMA182 F316/F316L	ASTM A182 F316/F316L
N05	GEAR BOX	DUCTILE IRON	DUCTILE IRON
N07d	STUD	ISO 8988.8	ISO 3506 A2-70
N08d	NUT	ISO8988	ISO 3506 A2-70
N30	BEARING	316L+PTFE	316L+PTFE
N30b	BEARING	316L+PTFE	316L+PTFE
N47	TOP FLANGE	ASTM A105N	ASTMA182F316/F316L
N73	SUPPORT PLATE	ASTM A572 Gr50	ASTMA240316/316L
N92	SUPPORT LEG	ASTM A572 Gr50	ASTMA572 Gr50
N93	LIFTING LUG	ASTM A572 Gr50	ASTMA572 Gr50

BSK Series Trunnion Mounted Ball Valve

Lipseal+Graphite Stem Seal

Parts & Material



Parts & Material


BSK Series Trunnion Mounted Ball Valve

Lipseal+Graphite Stem Seal

ITEM	PART	CRABON STEEL	STAINLESS STEEL
P01	BODY	ASTM A105N	ASTM A182 F316
P02	BODY CAP	ASTM A105N	ASTM A182 F316
P03	STEM	ASTMA705630	ASTM A182 F51
P05	GLAND FLANGE	ASTM A216 WCB	ASTMA351CF8M
P06	GLAND	ASTM A276 316/316L	ASTM A276 316/316L
P07	STUD	ASTMA193 B7M	ASTM A193 B8M CI2
P08	NUT	ASTM A1942HM	ASTM A194 8M
P07a	STUD	ASTMA193 B7M	ASTMA193 B8M CI2
P08a	NUT	ASTMA1942HM	ASTM A1948M
P10b	SCREW	ASTMA193 B7M	ASTMA193 B8M CI2
P14	STEM INJECTION	ASTMA182 F316/F316L	ASTM A182 F316/F316L
P14a	SEAT INJECTION	ASTM A182 F316/F316L	ASTM A182 F316/F316L
P15	DRAIN PLUG	ASTMA182 F316/F316L	ASTMA182 F316/F316L
P16	CHECK VALVE	ASTM A182 F316/F316L	ASTMA182 F316/F316L
P18	VENT VALVE	ASTM A182 F316/F316L	ASTMA182 F316/F316L
P19	COVER	ASTM A105N	ASTM A182 F316/F316L
C01	BALL	ASTM A182 F316/F316L+WC	ASTM A182 F316/F316L+WC
C02	SEAT	ASTMA182 F316/F316L+WC	ASTM A182 F316/F316L+WC
S01	GASKET	316L+GRAPHITE	316L+GRAPHITE
S01a	GASKET	316L+GRAPHITE	316L+GRAPHITE
S01c	GASKET	316L+GRAPHITE	316L+GRAPHITE
S02	O RING	FKM	FKM
S02a	O RING	FKM	FKM
S02e	O RING	FKM	FKM
S02h	O RING	FKM	FKM
S03c	LIPSEAL	PTFE+ELGILOY	PTFE+ELGILOY
S04	PACKING	GRAPHITE	GRAPHITE
W01	SPRING	ASTM B637 UNS N07750	ASTM B637 UNS N07750
W03	ANTI-STATIC PLUNGER	ASTM A276 316	ASTM A276 316
W04	ANTI-STATIC BALL	ASTM A276 316	ASTM A276 316
W05	ANTI-STATIC SPRING	ATSM A313 316	ATSM A313 316
W26a	THRUST WASHER	RPTFE	RPTFE
W46	SPACER RING	ASTMA276316/316L	ASTMA276316/316L
W53	SEAT FOLLOWER	ASTMA182F316/F316L	ASTMA182 F316/F316L
N05	GEAR BOX	DUCTILE IRON	DUCTILE IRON
N07d	STUD	ISO 898 8.8	ISO 3506 A2-70
N08d	NUT	ISO8988	ISO 3506 A2-70
N10c	BOLT	ISO 898 8.8	ISO 3506 A2-70
N30	BEARING	316L+PTFE	316L+PTFE
N30b	BEARING	316L+PTFE	316L+PTFE
N35	YOKE	ASTM A572 Gr50	ASTMA572Gr50
N73	SUPPORT PLATE	ASTMA572 Gr50	ASTMA240316/316L
N92	SUPPORT LEG	ASTM A572 Gr50	ASTM A572Gr50
N93	LIFTING LUG	ASTMA572 Gr50	ASTMA572Gr50

Metal-Seated Trunnion Mounted Ball Valve

Dimension&Weight



Class 150 Full bore -TM


Size		D		L				H1		H2		W		V		Weight	
				RF		BW											
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg
2	50	1.93	49	7.01	178	8.50	216	4.25	108	3.54	90			11.22	285	40	18
3	80	2.91	74	7.99	203	11.14	283	11.02	280	4.33	110	11.81	300			66	30
4	100	3.94	100	9.02	229	12.01	305	11.61	295	5.51	140	11.81	300			229	104
6	150	5.91	150	15.51	394	17.99	457	14.41	366	6.89	175	19.69	500			430	195
8	200	7.91	201	17.99	457	20.51	521	20.16	512	7.48	190	23.62	600			866	393
10	250	9.92	252	20.98	533	22.01	559	23.23	590	9.06	230	23.62	600			1113	505
12	300	11.93	303	24.02	610	25.00	635	26.22	666	11.61	295	27.56	700			1598	725
14	350	13.15	334	27.01	686	30.00	762	29.92	760	14.17	360	27.56	700			1984	900
16	400	15.16	385	30.00	762	32.99	838	32.68	830	16.73	425	29.92	760			2756	1250
18	450	17.17	436	34.02	864	35.98	914	36.22	920	18.50	470	29.92	760			4134	1875
20	500	19.17	487	35.98	914	39.02	991	39.49	1003	20.87	530	29.92	760			5181	2350
22	550	21.18	538	39.02	991	39.02	991	41.65	1058	23.43	595	29.92	760			6834	3100
24	600	23.19	589	42.01	1067	45.00	1143	43.90	1115	25.98	660	29.92	760			8609	3905
28	700	26.93	684	49.02	1245	52.99	1346	46.06	1170	28.54	725	29.92	760			12743	5780
30	750	28.94	735	50.98	1295	55.00	1397	48.23	1225	31.69	805	29.92	760			17163	7785
32	800	30.67	779	54.02	1372	60.00	1524	50.79	1290	34.53	877	31.50	800			20205	9165
34	850	32.68	830	57.99	1473	64.02	1626	53.15	1350	36.46	926	31.50	800			23810	10800
36	900	34.41	874	60.00	1524	67.99	1727	55.12	1400	38.39	975	35.43	900			28704	13020
40	1000	38.43	976	67.99	1727	67.99	1727	67.72	1720	40.16	1020	35.43	900			39793	18050

Class 150 Reduced bore -TM

Size		D		d		L				H1		H2		W		V		Weight	
						RF		BW											
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg
2"1-1/2	50*40	1.93	49	1.50	38	7.01	178	8.50	216	4.13	105	2.95	75			13.78	350	33	15
3"2	80*50	2.91	74	1.93	49	7.99	203	11.14	283	4.25	108	3.54	90			11.22	285	55	25
4"3	100*80	3.94	100	2.91	74	9.02	229	12.01	305	11.02	280	4.33	110	11.81	300			190	86
6"4	150*100	5.91	150	3.94	100	15.51	394	17.99	457	11.61	295	5.51	140	11.81	300			276	125
8"6	200*150	7.91	201	5.91	150	17.99	457	20.51	521	14.41	366	6.89	175	19.69	500			518	235
10"8	250*200	9.92	252	7.91	201	20.98	533	22.01	559	20.16	512	7.48	190	23.62	600			1005	456
12"10	300*250	11.93	303	9.92	252	24.02	610	25.00	635	23.23	590	9.06	230	23.62	600			1323	600
14"12	350*300	13.15	334	11.93	303	27.01	686	30.00	762	26.22	666	11.61	295	27.56	700			1786	810
16"14	400*350	15.16	385	13.15	334	30.00	762	32.99	838	29.92	760	14.17	360	27.56	700			2238	1015
18"16	450*400	17.17	436	15.16	385	34.02	864	35.98	914	32.68	830	16.73	425	29.92	760			2976	1350
20"18	500*450	19.17	487	17.17	436	35.98	914	39.02	991	36.22	920	18.50	470	29.92	760			4378	1986
22"20	550*500	21.18	538	19.17	487	39.02	991	39.02	991	39.49	1003	20.87	530	29.92	760			6173	2800
24"20	600*500	23.19	589	19.17	487	42.01	1067	45.00	1143	41.65	1058	23.43	595	29.92	760			7857	3564
28"24	700*600	26.93	684	23.19	589	49.02	1245	52.99	1346	43.90	1115	25.98	660	29.92	760			9535	4325
30"28	750*700	28.94	735	26.93	684	50.98	1295	55.00	1397	46.06	1170	28.54	725	29.92	760			14237	6458
32"30	800*750	30.67	779	28.94	735	54.02	1372	60.00	1524	48.23	1225	31.69	805	29.92	760			18569	8423
34"32	850*800	32.68	830	30.67	779	57.99	1473	64.02	1626	50.79	1290	34.53	877	31.50	800			21715	9850
36"32	900*800	34.41	874	30.67	779	60.00	1524	67.99	1727	53.15	1350	36.46	926	31.50	800			26786	12150
40"36	1000*900	38.43	976	34.41	874	73.03	1855	82.01	2083	57.48	1460	38.82	986	35.43	900			31415	14250

Dimension&Weight

Metal-Seated Trunnion Mounted Ball Valve



Class 300 Full bore -TM


Size		D		L				H1		H2		W		V		Weight	
				RF		BW											
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg
2	50	1.93	49	8.50	216	8.50	216	4.23	107.5	3.54	90			11.22	285	51	23
3	80	2.91	74	11.14	283	11.14	283	11.02	280	4.33	110	11.81	300			77	35
4	100	3.94	100	12.01	305	12.01	305	12.05	306	5.51	140	19.69	300			229	104
6	150	5.91	150	15.87	403	15.87	403	14.41	366	6.89	175	19.69	500			474	215
8	200	7.91	201	19.76	502	20.51	521	21.69	551	7.48	190	27.56	700			853	387
10	250	9.92	252	22.36	568	22.01	559	24.57	624	9.84	250	27.56	700			1411	640
12	300	11.93	303	25.51	648	25.00	635	27.60	701	12.44	316	29.92	760			1900	862
14	350	13.15	334	30.00	762	30.00	762	30.94	786	15.67	398	29.92	760			2976	1350
16	400	15.16	385	32.99	838	32.99	838	33.46	850	19.29	490	29.92	760			3439	1560
18	450	17.17	436	35.98	914	35.98	914	35.83	910	19.69	500	31.50	800			4643	2106
20	500	19.17	487	39.02	991	39.02	991	37.01	940	20.87	530	31.50	800			6173	2800
22	550	21.18	538	42.99	1092	42.99	1092	39.84	1012	23.11	587	31.50	800			7500	3402
24	600	23.19	589	45.00	1143	45.00	1143	42.52	1080	25.00	635	31.50	800			9259	4200
28	700	26.93	684	52.99	1346	52.99	1346	49.21	1250	31.10	790	31.50	800			13889	6300
30	750	28.94	735	55.00	1397	55.00	1397	51.97	1320	33.70	856	35.43	900			18827	8540
32	800	30.67	779	60.00	1524	60.00	1524	55.12	1400	36.22	920	35.43	900			22343	10135
34	850	32.68	830	64.02	1626	64.02	1626	59.69	1516	37.20	945	39.37	1000			24802	11250
36	900	34.41	874	67.99	1727	67.99	1727	64.06	1627	38.78	985	39.37	1000			31305	14200
40	1000	38.43	976	75.98	1930	75.98	1930	67.91	1725	40.47	1028	39.37	1000			42989	19500

Class 300 Reduced bore -TM

Size		D		d		L				H1		H2		W		V		Weight	
						RF		BW											
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg
2"1-1/2	50*40	1.93	49	1.50	38	8.50	216	8.50	216	4.13	105	2.95	75			9.84	250	42	19
3"2	80*50	2.91	74	1.93	49	11.14	283	11.14	283	4.23	107.5	3.54	90			11.22	285	68	31
4"3	100*80	3.94	100	2.91	74	12.01	305	12.01	305	11.02	280	4.33	110	11.81	300			190	86
6"4	150*100	5.91	150	3.94	100	15.87	403	15.87	403	12.05	306	5.51	140	19.69	500			357	162
8"6	200*150	7.91	201	5.91	150	19.76	502	20.51	521	14.41	366	6.89	175	19.69	500			584	265
10"8	250*200	9.92	252	7.91	201	22.36	568	22.01	559	21.69	551	7.48	190	27.56	700			939	426
12"10	300*250	11.93	303	9.92	252	25.51	648	25.00	635	24.57	624	9.84	250	27.56	700			1499	680
14"12	350*300	13.15	334	11.93	303	30.00	762	30.00	762	27.60	701	12.44	316	29.92	760			2017	915
16"14	400*350	15.16	385	13.15	334	32.99	838	32.99	838	30.94	786	15.67	398	29.92	760			3100	1406
18"16	450*400	17.17	436	15.16	385	35.98	914	35.98	914	33.46	850	19.29	490	29.92	760			3642	1652
20"18	500*450	19.17	487	17.17	436	39.02	991	39.02	991	35.83	910	19.69	500	31.50	800			4859	2204
22"20	550*500	21.18	538	19.17	487	42.99	1092	42.99	1092	37.01	940	20.87	530	31.50	800			6504	2950
24"20	600*500	23.19	589	19.17	487	45.00	1143	45.00	1143	39.84	1012	23.11	587	31.50	800			8029	3642
28"24	700*600	26.93	684	23.19	589	52.99	1346	52.99	1346	42.52	1080	25.00	635	31.50	800			9614	4361
30"28	750*700	28.94	735	26.93	684	55.00	1397	55.00	1397	49.21	1250	31.10	790	31.50	800			14356	6512
32"30	800*750	30.67	779	28.94	735	60.00	1524	60.00	1524	51.97	1320	33.70	856	35.43	900			19894	9024
34"32	850*800	32.68	830	30.67	779	64.02	1626	64.02	1626	55.12	1400	36.22	920	35.43	900			24140	10950
36"32	900*800	34.41	874	30.67	779	67.99	1727	67.99	1727	59.69	1516	37.20	945	39.37	1000			26550	12043
40"36	1000*900	38.43	976	34.41	874	75.98	1930	75.98	1930	64.06	1627	38.78	985	39.37	1000			33216	15067

Metal-Seated Trunnion Mounted Ball Valve

Dimension&Weight



Class 400 Full bore -TM


Size		D		L						H1		H2		W		V		Weight	
				RF		BW		RTJ											
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg
2	50	1.93	49	11.50	292	11.50	292	11.61	295	10.43	265	6.42	163	15.75	400			106	48
3	80	2.91	74	14.02	356	14.02	356	14.13	359	10.83	275	7.05	179	15.75	400			198	90
4	100	3.94	100	15.98	406	15.98	406	17.13	435	12.40	315	8.62	219	23.62	600			276	125
6	150	5.91	150	19.49	495	19.49	495	19.61	498	22.05	560	8.19	208	23.62	600			816	370
8	200	7.91	201	23.50	597	23.50	597	23.62	600	27.17	690	9.65	245	23.62	600			1499	680
10	250	9.92	252	26.50	673	26.50	673	26.61	676	24.92	633	12.05	306	23.62	600			2271	1030
12	300	11.93	303	30.00	762	30.00	762	30.12	765	26.18	665	13.74	349	29.92	760			2976	1350
14	350	13.15	334	32.52	826	32.52	826	32.64	829	24.37	619	15.75	400	27.56	700			4078	1850
16	400	15.16	385	35.51	902	35.51	902	35.63	905	29.06	738	17.72	450	29.92	760			4740	2150
18	450	17.17	436	38.50	978	38.50	978	38.62	981	30.83	783	19.76	502	35.43	900			6250	2835
20	500	19.17	487	41.50	1054	41.50	1054	41.73	1060	33.39	848	22.28	566	35.43	900			8025	3640
22	550	21.18	538	45.00	1143	45.00	1143	45.39	1153	37.56	954	23.31	592	39.37	1000			11728	5320
24	600	23.19	589	48.50	1232	48.50	1232	48.86	1241	40.04	1017	25.63	651	39.37	1000			15829	7180
28	700	26.93	684	55.00	1397	55.00	1397	55.51	1410	41.65	1058	27.83	707	39.37	1000			21032	9540
30	750	28.94	735	60.00	1524	60.00	1524	60.51	1537	44.69	1135	29.53	750	39.37	1000			23192	10520
32	800	30.67	779	65.00	1651	65.00	1651	65.63	1667	48.70	1237	30.94	786	43.54	1106			24802	11250
34	850	32.68	830	70.00	1778	70.00	1778	70.63	1794	51.34	1304	32.52	826	43.54	1106			28307	12840
36	900	34.41	874	74.02	1880	74.02	1880	73.82	1875	56.81	1443	35.51	902	43.54	1106			32518	14750
40	1000	38.43	976	85.43	2170	85.43	2170	85.43	2170	60.43	1535	38.86	987	43.54	1106			41226	18700

Class 400 Reduced bore -TM

Size		D		d		L						H1		H2		W		V		Weight	
						RF		BW		RTJ											
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg
2'1-1/2	50*40	1.93	49	1.50	38	11.50	292	11.50	292	11.61	295	8.11	206	5.71	145	15.75	400			88	40
3'2	80*50	2.91	74	1.93	49	14.02	356	14.02	356	14.13	359	10.43	265	6.42	163	15.75	400			168	78
4'3	100*80	3.94	100	2.91	74	15.98	406	15.98	406	17.13	435	10.83	275	7.05	179	15.75	400			231	105
6'4	150*100	5.91	150	3.94	100	19.49	495	19.49	495	19.61	498	12.40	315	8.62	219	23.62	600			617	280
8'6	200*150	7.91	201	5.91	150	23.50	597	23.50	597	23.62	600	22.05	560	8.19	208	23.62	600			1235	560
10'8	250*200	9.92	252	7.91	201	26.50	673	26.50	673	26.61	676	27.17	690	9.65	245	23.62	600			1653	750
12'10	300*250	11.93	303	9.92	252	30.00	762	30.00	762	30.12	765	24.92	633	12.05	306	23.62	600			2315	1050
14'12	350*300	13.15	334	11.93	303	32.52	826	32.52	826	32.64	829	26.18	665	13.74	349	29.92	760			3483	1580
16'14	400*350	15.16	385	13.15	334	35.51	902	35.51	902	35.63	905	24.37	619	15.75	400	27.56	700			4431	2010
18'16	450*400	17.17	436	15.16	385	38.50	978	38.50	978	38.62	981	29.06	738	17.72	450	29.92	760			5401	2450
20'18	500*450	19.17	487	17.17	438	41.50	1054	41.50	1054	41.73	1060	30.83	783	19.76	502	35.43	900			6702	3040
22'20	550*500	21.18	538	19.17	487	45.00	1143	45.00	1143	45.39	1153	33.39	848	22.28	566	35.43	900			10053	4580
24'20	600*500	23.19	589	19.17	487	48.50	1232	48.50	1232	48.86	1241	37.56	954	23.31	592	39.37	1000			13999	6350
28'24	700*600	26.93	684	23.19	589	55.00	1397	55.00	1397	55.51	1410	40.04	1017	25.63	651	39.37	1000			17670	8015
30'28	750*700	28.94	735	26.93	684	60.00	1524	60.00	1524	60.51	1537	41.65	1058	27.83	707	39.37	1000			22156	10050
32'30	800*750	30.67	779	28.94	735	65.00	1651	65.00	1651	65.63	1667	44.69	1135	29.53	750	39.37	1000			22222	10080
34'32	850*800	32.68	830	30.67	779	70.00	1778	70.00	1778	70.63	1794	48.70	1237	30.94	786	43.54	1106			24295	11020
36'32	900*800	34.41	874	30.67	779	74.02	1880	74.02	1880	73.82	1875	51.34	1304	32.52	826	43.54	1106			27337	12400
40'36	1000*900	38.43	976	34.41	874	85.43	2170	85.43	2170	85.43	2170	56.81	1443	35.51	902	43.54	1106			36486	16550

Dimension&Weight

Metal-Seated Trunnion Mounted Ball Valve




Class 600 Full bore -TM

Size		D		L						H1		H2		W		V		Weight	
				RF		BW		RTJ											
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg
2	50	1.93	49	11.50	292	11.50	292	11.61	295	10.43	265	6.42	163	15.75	400			106	48
3	80	2.91	74	14.02	356	14.02	356	14.13	359	10.83	275	7.05	179	15.75	400			198	90
4	100	3.94	100	17.01	432	17.01	432	17.13	435	12.40	315	8.62	219	23.62	600			331	150
6	150	5.91	150	22.01	559	22.01	559	22.13	562	22.05	560	8.19	208	23.62	600			970	440
8	200	7.91	201	25.98	660	25.98	660	26.14	664	27.17	690	9.65	245	23.62	600			1786	810
10	250	9.92	252	30.98	787	30.98	787	31.14	791	24.92	633	12.05	306	23.62	600			2723	1235
12	300	11.93	303	32.99	838	32.99	838	33.11	841	26.18	665	13.74	349	29.92	760			3571	1620
14	350	13.15	334	35.00	889	35.00	889	35.12	892	24.37	619	15.75	400	29.92	760			4486	2035
16	400	15.16	385	39.02	991	39.02	991	39.17	995	29.06	738	17.72	450	29.92	760			5688	2580
18	450	17.17	436	42.99	1092	42.99	1092	43.11	1095	30.83	783	19.76	502	35.43	900			7496	3400
20	500	19.17	487	47.01	1194	47.01	1194	47.24	1200	33.39	848	22.28	566	35.43	900			9612	4360
22	550	21.18	538	50.98	1295	50.98	1295	51.38	1305	37.56	954	23.31	592	39.37	1000			14065	6380
24	600	23.19	589	55.00	1397	55.00	1397	55.39	1407	40.04	1017	25.63	651	39.37	1000			18959	8600
28	700	26.93	684	60.98	1549	60.98	1549	61.50	1562	41.65	1058	27.83	707	39.37	1000			25000	11340
30	750	28.94	735	65.00	1651	65.00	1651	65.51	1664	44.69	1135	29.53	750	39.37	1000			27822	12620
32	800	30.67	779	70.00	1778	70.00	1778	70.63	1794	48.70	1237	30.94	786	43.54	1106			29762	13500
34	850	32.68	830	75.98	1930	75.98	1930	76.61	1946	51.34	1304	32.52	826	43.54	1106			33951	15400
36	900	34.41	874	82.01	2083	82.01	2083	82.56	2097	56.81	1443	35.51	902	43.54	1106			39021	17700
40	1000	38.43	976	85.43	2170	85.43	2170	85.43	2170	60.43	1535	38.86	987	43.54	1106			49383	22400

Metal-Seated Trunnion Mounted Ball Valve

Dimension&Weight



Class 900 Full bore -TM

Size		D		L						H1		H2		W		V		Weight	
				RF		BW		RTJ											
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg
2	50	1.93	49	14.49	368	14.49	368	14.61	371	12.20	310	4.53	115	19.69	500			220	100
3	80	2.91	74	15.00	381	15.00	381	15.12	384	11.10	282	4.69	119	15.75	400			331	150
4	100	3.94	100	17.99	457	17.99	457	18.11	460	15.75	400	7.87	200	23.62	600			485	220
6	150	5.91	150	24.02	610	24.02	610	24.13	613	18.98	482	8.78	223	29.92	760			1168	530
8	200	7.91	201	29.02	737	29.02	737	29.13	740	19.76	502	12.87	327	29.92	760			1351	613
10	250	9.92	252	32.99	838	32.99	838	33.11	841	20.83	529	14.69	373	31.50	800			2394	1086
12	300	11.93	303	37.99	965	37.99	965	38.11	968	36.81	935	13.15	334	35.43	900			6085	2760
14	350	12.68	322	40.51	1029	40.51	1029	40.87	1038	37.99	965	13.78	350	39.37	1000			6834	3100
16	400	14.69	373	44.49	1130	44.49	1130	44.88	1140	44.09	1120	18.90	480	39.37	1000			11376	5160
18	450	16.65	423	47.99	1219	47.99	1219	48.50	1232	46.54	1182	20.71	526	43.54	1106			16182	7340
20	500	18.54	471	52.01	1321	52.01	1321	52.52	1334	49.45	1256	22.80	579	43.54	1106			19892	9023

Class 900 Reduced bore -TM


Size		D		d		L						H1		H2		W		V		Weight	
						RF		BW		RTJ											
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg
2*1-1/2	50*40	1.93	49	1.50	38	14.49	368	14.49	368	14.61	371	8.54	217	4.69	119	15.75	400			157	71
3*2	80*50	2.91	74	1.93	49	15.00	381	15.00	381	15.12	384	12.20	310	4.53	115	19.69	500			220	100
4*3	100*80	3.94	100	2.91	74	17.99	457	17.99	457	18.11	460	11.10	282	4.69	119	15.75	400			331	150
6*4	150*100	5.91	150	3.94	100	24.02	610	24.02	610	24.13	613	15.75	400	7.87	200	23.62	600			485	220
8*6	200*150	7.91	201	5.91	150	29.02	737	29.02	737	29.13	740	18.98	482	8.78	223	29.92	760			1168	530
10*8	250*200	9.92	252	7.91	201	32.99	838	32.99	838	33.11	841	19.76	502	12.87	327	29.92	760			1351	613
12*10	300*250	11.93	303	9.92	252	37.99	965	37.99	965	38.11	968	20.83	529	14.69	373	31.50	800			2394	1086
14*12	350*300	12.68	322	11.93	303	40.51	1029	40.51	1029	40.87	1038	36.81	935	13.15	334	35.43	900			6085	2760
16*14	400*350	14.69	373	12.68	322	44.49	1130	44.49	1130	44.88	1140	37.99	965	13.78	350	39.37	1000			6834	3100
18*16	450*400	16.65	423	14.69	373	47.99	1219	47.99	1219	48.50	1232	44.09	1120	18.90	480	39.37	1000			11376	5160
20*18	500*450	18.54	471	16.65	423	52.01	1321	52.01	1321	52.52	1334	46.54	1182	20.71	526	43.54	1106			16182	7340

Class 1500 Full bore -TM

Size		D		L						H1		H2		W		V		Weight	
				RF		BW		RTJ											
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg
2	50	1.93	49	14.49	368	14.49	368	14.61	371	12.20	310	4.92	125	19.69	500			271	123
3	80	2.91	74	18.50	470	18.50	470	18.62	473	14.17	360	6.69	170	23.62	600			516	234
4	100	3.94	100	21.50	546	21.50	546	21.61	549	16.93	430	7.09	180	23.62	600			902	409
6	150	5.67	144	27.76	705	27.76	705	27.99	711	21.46	545	12.28	312	29.92	760			1984	900
8	200	7.56	192	32.76	832	32.76	832	33.11	841	27.17	690	15.75	400	29.92	760			2873	1303
10	250	9.41	239	39.02	991	39.02	991	39.37	1000	29.13	740	19.13	486	29.92	760			5538	2512
12	300	11.30	287	44.49	1130	44.49	1130	45.12	1146	31.10	790	21.10	536	29.92	760			7275	3300
14	350	12.40	315	49.49	1257	49.49	1257	50.24	1276	33.58	853	23.27	591	35.43	900			8466	3840
16	400	14.17	360	54.49	1384	54.49	1384	55.39	1407	35.91	912	24.41	620	35.43	900			9524	4320
18	450	15.98	406	60.51	1537	60.51	1537	61.38	1559	37.40	950	26.97	685	39.37	1000			10935	4960
20	500	17.87	454	60.51	1664	60.51	1664	66.38	1686	38.58	980	27.56	700	39.37	1000			12125	5500

Dimension&Weight

Metal-Seated Trunnion Mounted Ball Valve



Class 1500 Reduced bore -TM

Size		D		d		L						H1		H2		W		V		Weight	
						RF		BW		RTJ											
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg
2*1-1/2	50*40	1.93	49	1.50	38	14.49	368	14.49	368	14.61	371	12.20	310	4.92	125	19.69	500			245	111
3*2	80*50	2.91	74	1.93	49	18.50	470	18.50	470	18.62	473	14.17	360	6.69	170	23.62	600			485	220
4*3	100*80	3.94	100	2.91	74	21.50	546	21.50	546	21.61	549	16.93	430	7.09	180	23.62	600			714	324
6*4	150*100	5.67	144	3.94	100	27.76	705	27.76	705	27.99	711	21.46	545	12.28	312	29.92	760			1814	823
8*6	200*150	7.56	192	5.67	144	32.76	832	32.76	832	33.11	841	27.17	690	15.75	400	29.92	760			2873	1303
10*8	250*200	9.41	239	7.56	192	39.02	991	39.02	991	39.37	1000	29.13	740	19.13	486	29.92	760			4630	2100
12*10	300*250	11.30	287	9.41	239	44.49	1130	44.49	1130	45.12	1146	31.10	790	21.10	536	29.92	760			6426	2915
14*12	350*300	12.40	315	11.30	287	49.49	1257	49.49	1257	50.24	1276	33.58	853	23.27	591	35.43	900			7551	3425
16*14	400*350	14.17	360	12.40	315	54.49	1384	54.49	1384	55.39	1407	35.91	912	24.41	620	35.43	900			8873	4025
18*16	450*400	15.98	406	14.17	360	60.51	1537	60.51	1537	61.38	1559	37.40	950	26.97	685	39.37	1000			10194	4624
20*18	500*450	17.87	454	15.98	406	65.51	1664	65.51	1664	66.38	1686	38.58	980	27.56	700	39.37	1000			11023	5000

Class 2500 Full bore -TM

Size		D		L						H1		H2		W		V		Weight	
				RF		BW		RTJ											
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg
2	50	1.65	42	17.76	451	17.76	451	17.87	454	13.88	352.5	6.30	160	19.69	500			503	228
3	80	2.44	62	22.76	578	22.76	578	22.99	584	14.65	372	7.09	180	23.62	600			836	379
4	100	3.43	87	26.50	673	26.50	673	26.89	683	19.45	494	8.27	210	23.62	600			1248	566
6	150	5.16	131	35.98	914	35.98	914	36.50	927	26.69	678	14.96	380	29.92	760			2403	1090
8	200	7.05	179	40.24	1022	40.24	1022	40.87	1038	35.04	890	19.29	490	29.92	760			6195	2810
10	250	8.78	223	50.00	1270	50.00	1270	50.87	1292	37.64	956	19.76	502	35.43	900			9524	4320
12	300	10.43	265	55.98	1422	55.98	1422	56.89	1445	40.28	1023	22.05	560	39.37	1000			11486	5210

Typical application

- 1. Coal chemical industry: coal-to-liquids, coal-to-methanol, coal gasification.
- 2. High sour gas field with abrasive solids.
- 3. Shipbuilding, offshore.
- 4. Oxygen service.
- 5. Photovoltaic industry: polysilicon
- 6. Other working condition in high temperature or with abrasive solids.

Design and production features


Sealing structure of the seat
Bi-directional sealing of the valve. The seat is able to block the media from both sides of the valve, thus eliminating the limit of installing direction.
Preloading of belleville spring or cylinder spring to ensure sealing in low pressure.
Dust proof structure of the spring.

Live loading packing
The Belleville spring is added on gland flange to minimize need of packing retightening.

Choosing of sealing material
For all the gaskets and packing in relate to the sealing parts, the purity of the graphite is strictly controlled to lower the ignition lost rate and ensure the sealing performance in high temperature.

Design and analysis software

All the designs are verified in accordance with 3D Finite Element Analysis.
Neway has rich application experience in design software such as CAD, Solidworks, NX, Ansys, Fesafe, Cfdesign.



Valve Types		ASME Class			End Connections		Operator	
Symbol	Valve Type	Code	Class(LB)	Pressure	Symbol	End		Lever
BM	2-pcs Casting floating type	1	150	2.0Mpa	R	Raised face flanged end	G	Gear operator
BBM	2-pcs forging floating type	3	300	5.0Mpa	J	RTJ flanged end	M	Electric actuator
BSM	3-pcs forging trunnion mounted type	4	400	6.8Mpa	B	Butt-weld end	P	Pneumatic actuator
		6	600	10.0Mpa	S	Socket weld end	BS	Bare shaft
BSK	2-pcs forging trunnion mounted type(O-ring)	8	800	14.0Mpa	N	Screwed end	H	Hydraulic actuator
		9	900	15.0Mpa	SN	Socket weld/Screwed end	L	Gas over oil actuator
		15	1500	25.0Mpa			C	Gear operator(Operator forces≤350N)
		25	2500	42.0Mpa				

Product Warranty

Seller will replace without charge or refund the purchase price of products provided by Seller which prove to be defective in material or workmanship, provided in each case that the product is properly installed and is used in the service for which Seller recommends it and that written claim, specifying the alleged defect, is presented to the Seller within 18 months from the date of shipment or 12 months after installation, whichever occurs first. Seller shall in no event bear any labor, equipment, engineering or other costs incurred in connection with repair or replacement. The warranty stated in this paragraph is in lieu of all other warranties, either expressed or implied. With respect to warranties, this paragraph states Buyer's exclusive remedy and seller's exclusive liability.